



Input	Sensitivity for 15 W Empfindlichkeit für 15 W Indgang	Input Impedance -1 kHz Eingangsimpedanz -1 kHz Indgangsimpedanz -1 kHz	S/N Ratio 15 W S/N Verhältnis 15 W S/N Forhold 15 W
□ MAGNET	3 mV	47k Ohm	50 dB
□ CRYSTAL	500 mV	1M Ohm	60 dB
□ (3&5)	120 mV	0M Ohm	60 dB

SOCKET CONNECTIONS
Seen from the rear side of socket.

SOCKETVERBINDUNGEN
Anschlüsse von der Rückseite gesehen.

SOKKELFORBINDELSER
Set mod bund af sokkel.

Power supply, Netzeil, Nædel

T93
Push buttons shown in position LW and exterior aerial.
Drucktasten in Stellung LW und auswendig Antenne gezeigt.
Trykknapskifter overalt vist i stilling LB og udvendig antenne

Recommended impedance for stereophones: 400 Ohm, e.g. Beyer DT 96 A
Empfohlene Impedanz für Stereohörer: 400 Ohm, z.B. Beyer DT 96 A
Anbefalt impedans for stereohøvedtelefon: 400 Ohm, f.eks. Beyer DT 96 A

ARENA
TYPE T 260
HEDE NIELSEN A/S
8700 HORSSENS - TLF. 05-62 4711
4.875244 Maj 1969