

f2182 Kc/s		Cathode current, tube no.														Voltages measured in rel. to chassis				
		3	4a	4b	5a	5b	5c	5d	6	7a	7b	7c	7d	7x5	Grid	41 ÷Vg1	31 ÷Vg1	30 HT	19 Keying	
Stand- by, haller	Key open	35	0	0	0	0	0	0	0	0	0	0	0	0	0	0	54	24	590	+90
	Key down	34	46	46	45	45	40	0	0	0	0	0	0	0	0	0	50	23,5	570	0
	Key down	34	40	40	85	85	80	0	0	0	0	0	0	0	0	0	50	23,5	570	0
A <sub>1</sub>	Key open	35	0	0	0	0	0	0	0	0	0	0	0	0	0	0	54	24	0	+90
	Key down	33	0	0	0	0	0	40	110	110	110	110	440	20	0	0	50	23,5	0	0
A <sub>2</sub>	Key open	35	0	0	0	0	0	0	0	0	0	0	0	0	0	0	52	24	590	+90
	Key down	32	37	38	95	95	91	38	100	100	100	100	400	20	0	0	48	23	530	0
A <sub>3</sub> simplex	Key open	35	0	0	0	0	0	0	0	0	0	0	0	0	0	0	52	24	590	+90
	Key down	32	36	36	105	105	100	37	100	100	100	100	400	20	10	0	48	23	530	0
A <sub>3</sub> duplex	m = 0 %	32	42	43	40	40	35	38	105	105	105	420	20	0	0	0	49	23	540	0
	m = 90 %	32	36	36	105	105	100	37	100	100	100	400	20	0	0	0	48	23	530	0
A <sub>3</sub> duplex % power	m = 0 %	33	45	45	45	45	37	40	45	45	42	108	20	0	0	0	50	23,5	565	0
	m = 90 %	33	45	45	50	50	42	40	50	50	42	100	20	0	0	0	50	23,5	565	0
A <sub>1</sub>	Key down, aerial detuned	35	0	0	0	0	0	40	30	30	30	120	20	0	0	0	52	23,5	0	0

INGENIØRFIRMAET

M. P. PEDERSEN

A218

Tegn. af

Arkiv

Map

Dato

Tegn.

RR

22/58

NO