



## KUM480 HF-AERIAL

### Celwave KUM480 HF-Aerial

"SAILOR" NO.: KUM480 - E62.010

Anvendes til SAILOR T2031 Kysttelefoni og SAILOR Program 1000/B, 400 W Sender + ca. 5 m føde-tråd.  
Vagtmodtager SAILOR R501.

Kan bruges til modtager, hvor føde-tråd er ca. samme længde som pisken.

To be used in connection with SAILOR T2031 Coast Telephony and SAILOR Programme 1000/B, 400W Transmitter + approx. 5 metres of feed wire.

Watch Keeping Receiver SAILOR R501.

Can be used in connection with a receiver with a feed wire of approx. the same length as the whip.

#### Technical Specifications:

Frequency: 1.4-30.0 MHz

Max. Power Rating: 500 watt

Gain:

Termination Supplied: See drawing

Cable Impedance:

Max. VSWR:

Polarization: Vertical

Insulation Resistance: 10 E9 ohm

Static Capacity: Approx. 55 pF

#### Mechanical Specifications:

Max. Length: 4.80 metres

Weight: 2.000 kilos



#### A153 - E62.174 Mounting Clamp

For mast mounting of KUM480 aerial when the mast diameter is from 1.2 inches to 2 inches (30 mm to 51 mm).



#### A154 - E62.171 Mounting Clamp

For mast mounting of KUM480 aerial when the mast diameter is from 2 inches to 3.2 inches (51 mm to 80 mm).

