



* = SELECTED VALUE
 J = JUMPERS (INTERNAL)

| | | | | |
|---|--------------|----------------|-------------------|--|
| UNLESS OTHERWISE SPECIFIED | | CONTR. NO. | TE SYSTEMS | |
| DRILLED HOLE TOLERANCES ARE | 0.01 TO 0.02 | DRN BY | SCHEMATIC DIAGRAM | |
| 0.02 TO 0.05 | 0.01 | CHK BY | | |
| 0.05 TO 0.125 | 0.01 | DATE | | |
| 0.125 TO 0.250 | 0.01 | PROC. | | |
| 0.250 TO 0.500 | 0.01 | DESIGN | | |
| 0.500 TO 1.000 | 0.01 | APPROVED | | |
| MATCH FINISH 83/CR BETTER | | APPROVED | | |
| REMOVE ALL BURRS AND BREAK SHARP EDGES 0.005 R MAX. | | APPROVED | | |
| DIMENSIONS ARE IN INCHES | | SCALE | E | |
| FRACT & 1/64 ANGLES 50° | | CODE IDENT NO. | 1717 | |
| TOL. .004 = .01 .002 = .003 | | SCALE | 1/8"=1" | |
| DO NOT SCALE DRAWING | | REV | 1 | |