DUAL PRINTER CARD
USER'S MANUAL

1. DESCRIPTION

The Dual Printer card is a mini-size add-on card for 8088^{TM}, 286^{TM}, 386^{TM} and 486^{TM} systems with two printer ports for conneting the system with parallel devices, such as printer and plotter.

2. FEATURES

- Two Centronics parallel ports, one can be optional.
- Each parallel port can be set to LPT1, LPT2 Or LPT3.
- Each parallel port can use IRQ7 or IRQ5
- Easy I/O address and IRQ setting, all ports can be disabled.
- Mini size and low power consumption.

3. BOARD LAYOUT

JP1: I/O address

JP2: IRQ

LPT B
(Parallel Port B)

LPT A
(Parallel Port B)

4. SETTING THE I/O ADDRESS (JP1)

LPT B   LPT A

LPT 1
LPT 2
LPT 3

5. SETTING THE IRQ (JP2)

LPT B   LPT A

IRQ7
IRQ5

6. STANDARD I/O ADDRESS AND IRQ SETTING

Port Name	LPT1	LPT2	LPT3
I/O address	3BC	378	278
IRQ Setting	IRQ7	IRQ7	IRQ5 286^{TM}-486^{TM}
			IRQ7 8088^{TM}

* 8088^{TM}, 286^{TM}, 386^{TM} and 486^{TM} are trademarks of INTEL